

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

5 Listing of Claims:

Claim 1 (currently amended): A driving circuit of a liquid crystal display device comprising:

a substrate, comprising a plurality of scanning lines and a plurality of signal lines thereon;

10 at least two driver integrated circuit (IC) chips positioned on the substrate;
and

an impedance device electrically connected between the two driver IC chips for reducing a difference between respective input voltages being input into the two driver IC chips, the impedance device comprising a resistor and a capacitor,
15 the resistor and the capacitor being electrically connected in parallel with each other.

Claim 2 (canceled)

20 Claim 3 (currently amended): The driving circuit of ~~claim 2~~ claim 1 wherein the driver IC chips are used for outputting switching or addressing signals to the scanning lines.

Claim 4 (currently amended): The driving circuit of ~~claim 2~~ claim 1 wherein the driver IC chips are used for outputting image signals to the signal lines.

25

Claim 5 (canceled)

Claim 6 (currently amended): The driving circuit of ~~claim 5~~ claim 1 wherein the substrate comprises a first metal layer, a second metal layer, and an insulation layer
30 interposed between the first metal layer and the second metal layer.

Claim 7 (original): The driving circuit of claim 6 wherein the resistor comprises at

least a first conductive wire.

Claim 8 (original): The driving circuit of claim 7 wherein both of the first conductive wire and the scanning lines are parts of the first metal layer.

5

Claim 9 (original): The driving circuit of claim 7 wherein both of the first conductive wire and the signal lines are parts of the second metal layer.

Claim 10 (original): The driving circuit of claim 6 wherein the scanning lines are parts of the first metal layer, and the signal lines are parts of the second metal layer.

10

Claim 11 (original): The driving circuit of claim 10 wherein the capacitor comprises a second conductive wire that is a part of the first metal layer, a third conductive wire that is a part of the second metal layer, and the insulation layer interposed between the second conductive wire and the third conductive wire.

15

Claim 12 (original): The driving circuit of claim 1 wherein a transparent conductive layer is positioned between each of the driver IC chips and the impedance device, each of the driver IC chips being capable of receiving an approximately identical input voltage through each of the transparent conductive layers.

20

Claim 13 (original): The driving circuit of claim 1 wherein the liquid crystal display device is designed by applying wiring on array (WOA) technology, and the liquid crystal display device is driven by the driving circuit.

25

Claim 14 (original): A liquid crystal display device comprising:
a first substrate;
a second substrate opposite to and in parallel with the first substrate, the second substrate comprising a plurality of pixels arranged in a matrix; and
a driving circuit positioned on the second substrate for outputting signals to the pixels, the driving circuit comprising:
at least two driver integrated circuit (IC) chips positioned on the

30

second substrate; and

an impedance device electrically connected between the two driver IC chips, the impedance device having a resistor and a capacitor being electrically connected in parallel with each other for reducing a difference
5 between respective input voltages being input into the two driver IC chips.

Claim 15 (original): The liquid crystal display device of claim 14 wherein the driving circuit is a scanning line driving circuit.

10 Claim 16 (original): The liquid crystal display device of claim 14 wherein the driving circuit is a signal line driving circuit.

Claim 17 (original): The liquid crystal display device of claim 14 wherein the resistor comprises at least a first conductive wire.

15 Claim 18 (original): The liquid crystal display device of claim 14 wherein the capacitor comprises a second conductive wire, a third conductive wire, and an insulation layer interposed between the second conductive wire and the third conductive wire.

20 Claim 19 (original): The liquid crystal display device of claim 14 wherein a transparent conductive layer is positioned between each of the driver IC chips and the impedance device, each of the driver IC chips being capable of receiving an approximately identical input voltage through each of the transparent conductive
25 layers.